### **DATASHEET / BROCHURE**

# Epson TM-T20III (012): Ethernet, PS, Blk, EU



This entry-level thermal POS receipt printer provides a costeffective POS solution with fast print speeds and economical features.

The combination of its fast print speeds, high reliability and economical operation, make this printer a must-have for small retail and speciality stores, hospitality venues and grocery stores.

## Affordable

This easy-to-use model is our entry-level POS receipt printer and has an 80mm printing width. Its Automatic Paper Reduction feature reduces top and bottom margins, line feed width and barcode height, allowing for flexible receipt printing. This monitors and controls the amount of paper used. Paper costs are minimised by printing the top logo of the next receipt before cutting, so the top margin is further reduced by 12mm.

#### Reliable

With the mean time between failures (MTBF) of 360,000 hours and a mechanism life of 15 million lines, you can rely on the TM-T20III in high-volume printing environments.

## Flexible

The TM-T20III comes with a built-in USB interface. You can select from two models: 1) USB + Serial, 2) Ethernet, making the model a long-term investment as it is possible to switch connectivity at any time.

#### Fast

Its print speed of 250mm/sec can save you time and its competitive price and running costs can save you money; ideal for when you need to beat queues quickly.

#### **KEY FEATURES**

- Economical Automatic paper reduction function
- Reliable
   Mechanism life of 15 million lines
- Fast print speed
  Print speed of 250mm/sec
- Flexible connectivity
  Two models: 1) USB + Serial 2) Ethernet
- Peace of mind
   Epson is Europe's number one POS printer manufacturer<sup>1</sup>



### PRODUCT SPECIFICATIONS

Print speed 250 mm/sec **FONTS & STYLES** Column capacity Paper width 80 mm, 48 / 64 PAPER  $79.50 \pm 0.50$  (W) mm x dia 83.00 mm, Paper size  $57.50 \pm 0.50$  (W) mm x dia 83.00 mm **FONTS & STYLES** 

Print Speed 250 mm/sec Print Speed receipt 250 mm/sec **Printing Font** ANK

Paper width 80 mm, 48 / 64 Column capacity receipt

95 Alphanumeric, 18 set International, 128 x 43 Graphic Character set

Characters per inch 22.6 cpi / 16.9 cpi Dot density 203 dpi x 203 dpi Colour Printing Black

**Printing Characters** Text (incl. Euro symbol), Graphics, Barcode

INTERFACES

Ethernet interface (100 Base-TX / 10 Base-T), Drawer kick-out Interfaces

DATA BUFFER

4 kB or 45 Bytes Data Buffer

POWER

Power Supply AC adapter, C1 Power Consumption standby: 0.1 A, Mean: 1.8 A

24 V Operating Voltage

**GENERAL** 

Product dimensions 140 x 199 x 146 mm (Width x Depth x Height)

Product weight 1.7 kg Colour Black (EBCK)

Installation horizontally, vertically, vertically with wall hanging bracket

D.K.D. function (2 drivers) Interface connectors Noise Level Operation: 55 dB (A)

Operation 10% - 90%. Storage 10% - 90% Humidity Temperature Operation 5° C - 45° C, Storage -10° C - 50° C

STANDARDS COMPLIANCE

FCC class A, CE marking, EN55022 Class A

UL, CSA, TÜV Safety standards

OTHER FEATURES

Cutter Partial Cut

Paper End Sensor, Paper Near End Sensor

Paper Saving Function Yes

# **OPTIONAL ACCESSORIES**

• OT-BZ20-634: Optional External Buzzer C32C890634

## LOGISTICS INFORMATION

SKU	C31CH51012
EAN code	8715946669656
Dimensions Single Carton	490 x 400 x 295 mm
Carton Weight	0 Kg
Country of Origin	Philippines
Layer	16 Units
Layer Block	24 Units

For more information please contact:

Home users: 0343 90 37766 Business users\*: 0871 42 37766 Republic of Ireland: 01 436 7742

Or visit us at https://www.epson.co.uk/contactus
\* 10p per minute plus network extras.

www.epson.co.uk www.epson.ie

Epson TM-T20III (012): Ethernet, PS, Blk, EU

#### WHAT'S IN THE BOX

- CD Manual
- Main unit
- Power switch cover
- Roll paper
- Rubber feet
- USB cable
- Wall mounting bracket
- Warranty document
- Paper roll spacer
- Setup guide
- AC adapter, C1
- EURO AC cable

1. Number one POS printer manufacturer based on shipments for FY17 (IDC 2018)

