





FEATURES

Seamless barcode scanning.

An omnidirectional Newland scan engine ensures responsive scanning of 1D and 2D barcodes. Both trained employees and inexperienced customers will be able to scan printed and digital barcodes with ease.

Enterprise-level Android OS.

Running Android, the NQuire 300 provides your team with endless development possibilities and your customers with a device that is intuitive in use. Looking up product information, scanning a ticket, checking a price or making a purchase is quick and simple, even for inexperienced users.

MDM software.

Keep track of devices in the field with Newland's mobile device management (MDM) software.

Endless versatility.

Equipped with a variety of features that make it easy to adapt the NQuire 300 to your application. The device has a built-in HF RFID reader and data can be transmitted through Ethernet, WiFi and BT (optional). An external USB and GPIO port provide the possibility to connect an external device, e.g. a handheld scanner.

Mount anywhere.

With dimensions of 140 x 139.5 x 61 (HxWxD) and compliance with VESA 75 standards, the NQuire 300 can easily be mounted on any shelf, pole or wall.



NQuire 300 with VESA 75 standard.

Application Scenarios

NQuire 300 Android micro kiosk

			NQuire301	NQuire304
Performance	CPU		1.4 GHz 32-bit ARM A9 CPU	
	Operating System		Android 4.4.2	
	Memory		RAM: 1GB DDR3	
			Flash: 4GB	
			Support Micro SD up to 32GB	
	Display		4.3"480*272 TFT LCD Display with 5-point capacitive touch panel	
	Speaker		88dB (850Hz~20KHz) dual-channel stereo sound	
	Network	Ethernet	10/100Mbps Ethernet	
	Network -	WiFi	IEEE 802.11b/g/n	
	BT (optional)		Bluetooth 4.0 LE	
	RFID		ISO/IEC 14443 A/B ISO/IEC 15693; MIFARE 1K/4K; MIFARE DESFire; Sony FeliCa	
	Ports	USB	2 x USB2.0 ports (One supports Host, the other supports Host & Slave)	
	-	GPIO	Programmable GPIO (2 in - 2 out)	
	Symbologi	es	1D	2D
			1D: EAN-13, EAN-8, UPC-A, UPC-E, ISSN, ISBN,	2D: PDF417, Data Matrix, QR Code,
			Codabar, Code 128, Code 93, ITF-6, ITF-14,	Chinese Sensible Code.
			Interleaved 2 of 5, Industrial 2 of 5, Standard	1D: EAN-13, EAN-8, UCC/EAN-128, UPC-A, UPC-E
			2 of 5, Matrix 2 of 5, GS1 Databar, Code 39,	ISBN, Codabar, Code 128, Code 93, ITF-6,
			Code 32, Code 11, MSI-Plessey, Plessey	ITF-14, Interleaved 2 of 5, Industrial 2 of 5,
				Standard 2 of 5, Matrix 2 of 5, GS1 Databar,
				Code 39, Code 32, Code 11, MSI-Plessey,
				Plessey.
	Resolution		≥4mil	≥3mil
	Typical De	pth of Field	Code 39 (5mil): 60mm-145mm	Code 39 (5mil): 34mm-125mm
			EAN-13 (13mil): 50mm-290mm	EAN-13 (13mil): 55mm-210mm
			Code 128 (10mil): 34mm-260mm	Code 128 (10mil): 51mm-160mm
				PDF417 (6.7mil): 43mm-100mm
				Data Matrix (10mil): 44mm-92mm
				QR Code (15mil): 35mm-130mm
Mechanical/	Power Consumption		6W	
Electrical	Power Adapter		DC9-25V, 2000mA	
	P-o-E		Power-over-Ethernet IEEE 802.3af	
	Dimensions		140(H) × 139.5(W) x61(D)mm	
	Weight		403g	
Environmental	Operating Temperature		0°C to 50°C (32°F to 122°F)	
	Storage Temperature		-20°C to 55°C (-4°F to 131°F)	
	Operating Humidity		5% to 90% (non-condensing)	
	Storage Humidity		5% to 95% (non-condensing)	
Accessories	VESA75 Mount		The NQuire300 complies with standard VESA 75 bracket, enabling easy mounting on shelves and walls.	
Accessories	Power Adapter		Output: DC12V, 2A; Input AC100~240V, 50~60Hz	
Accessories	Power Ada	pter	Output: DC12V. 2A: Inp	out AC100~240V, 50~60HZ

Newland EMEA HQ

+31 (0) 345 87 00 33 info@newland-id.com newland-id.com

D-A-C-H

+49 (6) 182 82916-16 info@newland-id.de

Benelux

+31 (0) 345 87 00 33 benelux@newland-id.com

Italy

+39 (0) 342 0562227 italy@newland-id.com **United Kingdom** +44 (0) 7771 631387

info@newland-id.co.uk

Turkey +90 (0) 544 538 40 49 turkey@newland-id.com

South Africa

Gauteng: +27 (0) 11 553 8010 Cape Town: +27 (0) 21 9140819 info@newland-id.co.za

France

+39 (0) 345 8804096 france@newland-id.com

Ibérica

+34 (0) 93 303 74 66 info@newland-id.es

Nordic & Baltic +46 (0) 70 88 47 767 nordic@newland-id.com Russia

+31 (0) 345 87 00 33 russia@newland-id.com

Middle East +39 (0) 345 8804096

middleeast@newland-id.com

Iran +90 (0) 544 538 40 49 iran@newland-id.com